



Acuros[®] CQD[®] 1280 GigE eSWIR Camera

Acuros[®] CQD[®] cameras are the highest pixel resolution SWIR cameras sold commercially, enabling users to see features with the finest details. Our novel CQD sensors deliver full visible to **eSWIR** response, achieving lowest cost per megapixel. Our new Acuros **eSWIR** cameras built with 640x512, 1280x1024, or 1920x1080 focal plane arrays, delivering truly high resolution, and very high detectivity imaging to 2000nm. This novel capability opens up new applications for chemical sensing, surveillance imaging, plastic sorting, thermal imaging and more.

Specifications:

Electro-Optical Specifications:

Sensor	Acuros [®] CQD [®] sensor
Temperature stabilization	Single-stage thermo-electric cooler
Sensor array format	1280 x 1024
Resolution	1.31 megapixels
Spectral band	350 nm - 2000 nm
Array size	19.2mm x 15.4 mm, 24.6 mm diagonal
Pixel pitch	15 μ m x 15 μ m
Max frame rate at full resolution	88 fps (8 bit), 45fps (10 bit, 12 bit)
Pixel operability	99.5% typical
Bit depth	8, 10, 12 bit selectable
Integration type	Snapshot global shutter
Trigger	External TTL
Integration time	10 μ sec to 30 msec
Dynamic range	65 dB typical
Windowing	Array centered
Windowing frame rate	Scales inversely with window size
Binning arrays	2 x 2, 4 x 4
Non-uniformity correction	2-point non-uniformity correction
Temporal dark noise	< 210 electrons rms typical
Detectivity	See typical detectivity curve.

Features:

- HD resolution
- TEC cooling
- Low noise
- Fast frame rate
- Visible-**eSWIR**
- GigE Vision
- High value

Applications:

- Hydrocarbon detection
- Chemical sensing
- Medical imaging
- Plastic sorting
- Hyperspectral
- High resolution
- Thermal imaging
- Surveillance
- Machine vision
- Silicon inspection
- Instrumentation



SWIR[®]

VISION SYSTEMS

High Definition. SWIR Vision.

Specifications:

Environmental & power specifications, typical performance

Operating case temperature	-20 °C to +55 °C
Power consumption	6.5 watts, full frame rate, 40 °C case temp.
Power supply voltage	6-16 VDC
Regulatory compliance	CE mark

Mechanical specifications

Dimensions excluding lens	6.1 x 6.1 x 10.3 cm (C-Mount)
Weight excluding lens	508 grams with C-mount adaptor, 594g (F-mount)
Lens mounts	C-, F-Mount, M42 (C-Mount flange-back distance)
Power connector	Hirose 12-pin, HR10A-10R-12PB (71)
Trigger connector	BNC

Software and user interface

Software development kit	Windows GUI and SDK
GenICam compliance	Yes
Interface	GigE Vision

Export compliance

US export designation	EAR-99. No license required for lawful export
-----------------------	---

Ordering

Part numbers	Acuros-1280-GigE-002
--------------	----------------------




C-mount, F-mount,
and M-42 Lens
Mounts




GigE Vision
Interface

Acuros CQD SWIR camera images



Typical Detectivity Performance



- a. Acuros 640: imaging through maritime rain event
- b. Acuros 640: imaging through pharmaceutical vial labels
- c. Acuros 1280: alignment mark in bonded wafers
- d. Acuros 1920: mag image of semiconductor chip edge




SWIR[®]

VISION SYSTEMS

High Definition. SWIR Vision.

Mechanical Drawings



D-A-CH

Laser 2000 GmbH
82234 Wessling
Tel. +49 8153 405-0
info@laser2000.de
www.laser2000.de

FRANCE

Laser 2000 SAS
33600 Pessac
Tel. +33 5 57 10 92 80
info@laser2000.fr
www.laser2000.fr

IBERIA

Laser 2000 SAS
28034 Madrid
Tel. +34 617 308 236
info@laser2000.es
www.laser2000.es

NORDICS

Laser 2000 GmbH
11251 Stockholm
Tel. +46 733 12 13 66
info@laser2000.se
www.laser2000.se